

# ES290 IP Innovative VoIP Phone User Manual



## Escene Communication Co.Ltd

### **INDEX**

1. Getting Started4
About4
Feature Highlights4
2. Set up the Phone5
3. Phone User Interface6
3.1 Hardware Component Instructions6
3.2 Phone Screen Display Features8
3.3 Basic Network Settings9
3.4 SIP Account Settings10
3.5 Basic Features11
3.5.1 Making a Call11
3.5.2 Anonymous Call12
3.5.3 Redial12
3.5.4 Call Log12
3.5.5 Making Calls to Contact
3.5.6 Multi-lines to Answer the Call13
3.5.7 Auto-Answer
3.5.8 Ending a Call14
3.5.9 Using Hold and Recover (Switch Calling Line)14
3.5.10 Transferring Calls15
3.5.11 Using Mute15
3.5.12 Do Not Disturb
3.5.13 3-way Conference16
3.5.14 Voice Mail17
3.6 Advanced Settings17
3.6.1 Using the phone book17
3.6.2 Using Call Logs20
3.6.3 Peer-to-Peer21
3.7 Keypad Setting21
3.7.1 Language Setting21
3.7.2 Message22
3.7.3 Time & Date22
3.7.4 Ring Tone and Volume Setting23
3.7.5 Searching Phone Book23
3.7.6 Cannot Set the Features with Keypad23
4. WEB User Interface24
www.escene.ru

Main Interface-Phone Status	24
4.1 Net Work	25
4.1.1 LAN Port	25
4.1.2 PC Port	27
4.1.3 Advanced	28
5 SIP Account	29
5.1Basic	29
5.2 Call	30
5.3 Security	31
6 Phone Setting	
6.1 Basic	
6.1.1 Time Settings	
6.1.2 Call	
6.1.3 VoIP Call Forward	
6.1.4 QoS	
6.2 Advanced	
6.2 .0 Audio	
6.3 Line Keys	
6.4 Function Keys	
6.5 Soft Key	
6.6 Dial Plan	
6.7 IP Strategy	
7 Phone Book	
7.1 Group	
7.2 Contact	
7.3 LDAP	
7.4 Ban List	
8 Phone Maintenance	
8.1 Basic	
8.1.1 HTTP Upgrade	
8.1.2 FTP Upgrade	
8.1.3 TFTP Upgrade	
8.1.4 Default Setting	
8.1.5 Reboot	
8.2 Advanced	
8.2.1 Log	
8.2.2 Auto Provision	
9 Password	
10 WEB Other Settings or Information - Appendix	
10.1 WEB User	
10.2 Multi-Language	51
10.3 Note Tips	51

# 1. Getting Started

#### **About**

Escene ES290 is a highly innovative based VoIP phone, It can perfectly satisfy all kinds of businessmen's communications. ES290 integrates with 128x64 pixel graphic LCD, a large resolution display, elegant and intuitionist user interface, which you can perfectly experience. ES290 delivers HD audio quality with HD handset, HD speaker and HD codec (G.722), it rich features can effectively improve the communications in working. ES290 quite meets the demands of SMEs, Home Office and ISP applications.

#### **Feature Highlights**

#### a) Multi-Language

The LCD display supports Multi-Language.

#### b) HD Voice

Special voice processing technology, high-fidelity voice quality, HD encoding, HD Handset, ensure clear, realistic smooth communication.

#### c) Senior Calling Ability

2 lines with double color(GREEN & RED) LEDs, Synchronously control or manage 2 calls, Call queue, Switch between lines. Multi-parties conference, call transfer.

#### d) All kinds of Phone Book

It supports XML Personal Phone Book\LDAP\Enterprise Phone Book etc. This feature satisfies customer's phone book requirements.

- e) Support HTTP\TFTP\Auto-Provision.
- f) Support POE(Remark: ES290-PN) / Power Adapter / USB (Standard DC 5V).
- g) 2-angle adjustable bracket, wall-mountable

# 2. Set up the Phone

#### a) Packing List:

Check the packing list before installation, if you find anything missing, contact your system administrator.

- 1\*ES290 IP Phone
- 1\*Handset
- 1\* Handset Cord
- 1\*Ethernet Cable
- 1\*Phone Bracket
- 1\*Quick Setup Guide
- 1\*Manufacturer Certification


#### b) Phone Installation:

This section introduces how to install the phone with the components in the packing list:


- Attach the Bracket
- Connect the Handset and optional Headset
- Connect the Network and Power


#### **Attach the Bracket**

Pls follow the following step "a" to "b", firstly let the part 1 of the bracket join to the phone, and then let the part 2 of the bracket join to the lower holder.



**Connect the Handset and optional Headset** 






#### **Connect the Network and Power**

You have two options for power supply. Your system administrator will advise you which one to use.

- AC power adapter
- POE(Power over Ethernet) IEEE802.3af
- USB(Standard DC 5V)

NOTES: Pls make sure your phone support POE feature. You can check the label on the back of the phone, for example "Model: ES290-PN Rev:2.1.0", the P means it support POE feature.




Note: If POE works, the phone doesn't need to connect to the AC power adapter. Make sure the Ethernet cable and switch/hub is POE compliant.

## 3. Phone User Interface

## **3.1 Hardware Component Instructions**

The main hardware components of the ES290 IP Phone are the LCD screen and the keypad.



#### Hardware component instructions of the ES290 IP Phone are:

Tidia	Traidware component instructions of the E3230 IF Phone are.					
	ITEM	DESCRIPTION				
1	LCD Screen	Displayed information about calls, messages, soft keys, time, date				
		and other relevant data:				
		Call information — caller ID, call duration				
		• Icons (e.g. DND)				
		Missed calls or second incoming caller's information				
		•Time and date				
2	Light Status	Red-Flashing: There is an incoming call or be Hold.				
		Red-Steady: Hook-off. or be in an usual conversation				
3	Line Key	Green-Steady: There is a conversation making on the line				
		Red-Flashing: There is call coming in				
		Green-Flashing: The line is on hold				
		Dark: Accounts are idle				
4	Soft Key	Labels automatically to identity their context-sensitive features				
5	OK Key	Confirm the action				
6	Navigation Key	Scroll through the displayed information, and in the idle feature:				
		UP: Open the "All CONTACT LOG"				
		DOWN: Open the "MISSED CALL"				
		RIGHT: Open the "RECEIVED CALL"				
		LEFT: Open the "DAIL CALL"				
7	C Key	Cancels actions or rejects an incoming call, and the other feature:				

		In the idle: Open the "Phone Status".				
		Diagnosis: Press and hold 3 second to open "Hardware Diagnosis".				
		MUTE: "MUTE" feature is enabled if you press it while the				
		conversation making on the phone.				
8	Functions Key	Conference\Redial\Transfer\Hold				
9	Speaker Key	Toggles the hands-free speaker phone mode.				
10	Keypad	Provides the digits, letters and special characters in				
		context-sensitive applications.				
11	Headset Key	Toggles and indicates the headset mode.				
12	Message Key	Indicates and accesses voice messages.				
13	Volume Key	Adjusts the volume of the handset, headset, speaker and ringer				

## 3.2 Phone Screen Display Features

If the phone has successfully started up and after using, the idle LCD display will show information as below:





	ITEM	DESCRIPTION			
1	TIME & DATE	TIME & DATE display in the middle of the screen.			
2	Auto-Answer icon	Enable this feature, it will display "AA" at the top right corner.			
3	Missed Call	Missed Call under the TIME in the middle of screen			
4	Line Status	There are four status as below:			
		a. LAN:Disconnect:Disconnect the network			
		b. Account failed to register			
		c. :Account successfully registered			
		d. Account successfully registered and DND feature is enabled. The DND icon also will display at the top right corner.			
5	Soft Key Area	Labels automatically to identity their context-sensitive features			
6	Screen Top Icon	The Screen Top Icon from left to right is:			
		: Handset Hand on status			

:Speaker Hand on status
:Headset Hand on status
:Call MUTE
:Missed Call
:Call Forward
:Text Message
:Keypad Lock
:Network is unavailable

## 3.3 Basic Network Settings

The phone supports Three Modes of Network Setting. Include PPPoE\Static IP\DHCP.

#### **DHCP Setting**

Feature	Operating Steps		
DHCP	Press OK or MENU> System Settings> Advanced Settings>		
	Password(Default is Empty)> Network> LAN Port		
	Press LAN Port to login in to the menu		
	Select "DHCP" mode		
	Press "Enter" key		
	Set the DNS\web port\telnet port		
	Press "Save" key to make it work		
	Tips "Network is changed, press OK reboot "		

#### **Static IP Setting**

Feature	Operating Steps		
Static IP	Press <b>OK</b> or <b>MENU&gt; System Settings&gt; Advanced Settings&gt;</b>		
	Password(Default is Empty)> Network> LAN Port		
	<ul> <li>Press LAN Port to login in to the menu</li> </ul>		
	Select "Static" mode		
	Press "Enter" key		
	<ul> <li>Set the IP\Mask\GW\DNS\web port\telnet port</li> </ul>		
	Press "Save" key to make it work		
	Tips "Network is changed, press OK reboot "		

#### **PPPoE Setting**

Feature	Operating Steps		
PPPoE	Press OK or MENU> System Settings> Advanced Settings>		
	assword(Default is Empty)> Network> LAN Port		
	Press LAN Port to login in to the menu		
	Select "PPPoE" mode		
	Press "Enter" key		
	Set the User Name\Password\web port\telnet port		
	Press "Save" key to make it work		
	Tips "Network is changed, press OK reboot "		

## 3.4 SIP Account Settings

ES290 IP phone makes calls based on sip accounts, It can support Single account or Multi-account, Each account can be configured to the different SIP server.

Multi-acco	unt, Ea	ach acc	count can be configured to the different SIP server.			
If you want to			Then			
Create	an	SIP	1) Select "System setting" > "Advanced setting";			
account			2) Enter the password required (The default is empty);			
			3) Select "SIP" > "Account sip";			
			4) Select one of the account you want to setting, you can			
			configure the following parameters			
			- <b>Enable account*</b> : Select Enable			
			-Number of lines: Default is 2			
			-Description: description of this account			
			- <b>Display Name</b> : The name displayed on the screen			
			-Authentication user: the Authenticated users are matched			
			with the SIP server.(The default With the same account)			
			- <b>Account*</b> : the account matches with the SIP			
			server.(extension number)			
			- <b>User pass word*</b> : the user password matches with the SIP			
			server			
			-SIP Server*: The primary SIP server, all calls through this			

	server			
	-Out Bound Server: The out bound SIP server			
	-STUN Type: Enable/Disable STUN feature -STUN: Input STUN URL			
	<ul> <li>-Auto Answer: Enable/Disable this account auto answer feature</li> <li>* Note: When you finish the setting, you can press Save to make it</li> </ul>			
	work, and then you can see the status icon in the LCD idle.			
	The parameters with the * mark must be set.			
Disable sip account	1) Select "System setting" > "Advanced setting";			
	2) Enter the password required (The default is empty);			
	3) Select "SIP" > "Account sip";			
	4) Select "Enable account" > "Disable";			
	5) Select "Save" to saves settings			

### 3.5 Basic Features

# 3.5.1 Making a Call

Here are some easy ways to place a call on SayHi IP Phone:

If you want	Then		
to			
Place a call using	Pick up the handset	1) You can hear dial tone;	
the handset		2) Enter a number; 3) Press # button (default),	
Place a call using	Press <b>Speaker</b> button	-or wait 5s (default), then it send the	
a speakerphone		number automatically.	
Place a call using	Put on your headset,		
a headset	active <b>Headset</b> button		
	so that the status light is		
	Red, and then do as		
	using speakerphone		

## 3.5.2 Anonymous Call

You can use anonymous call feature to block the identity and phone number from showing up to the called party when you call someone. E.g, you want to call to consult some of the services, but you don't want to be harassed.

Enable Anonymous Call	Press OK or MENU> Function Setting> Anonymous			
	Press <b>Enter or OK</b> button ,			
	-You can select which Account want to use, enable/disable			
	this feature and enable/disable reject anonymous			

#### **3.5.3 Redial**

To redial the last placed call from your phone

Redial	Press <b>REDIAL</b> button to dial the last number
	-or press <b>Navigation button-Left</b> > "Dialed number", select
	a number, and press Dial

## 3.5.4 Call Log

Dial from a call log	1) Press <b>MENU</b> or <b>OK</b> button > "Call history", you can select
	"All Calls", "Missed calls", "Received calls" and "Dialed
	numbers",
	- or press <b>Navigation button</b> (in Standby interface) > select
	"All Calls"( <b>up</b> ) "Missed calls"( <b>down</b> ), "Received calls"( <b>left</b> )
	and "Dialed numbers" ( <b>right</b> )
	2) Then press Dial button.
	NOTE: You also can press the "log" to login this menu
	when in the idle.

# 3.5.5 Making Calls to Contact

You can also dial a contact from the Personal Phone Book.

Placing Contacts	Calls	to	1) Press <b>MENU</b> or <b>OK</b> button > "Phone Book", you can select
Contacts			"Personal Phone Book", "Enterprise Phone Book", "LDAP"
			and "Black List",
			- or press <b>Navigation button</b> (in Standby interface) > select
			the desired contact.
			2) Then press Dial button.
			NOTE: You also can press the "DIR" to login this menu
			when in the idle.

### 3.5.6 Multi-lines to Answer the Call

Multi-lines to Answer the Call	1) Another <b>Line</b> button is Red and flashing, Light strip is
the can	Red and flashing;
	2) Press the flashing Line button to answer (at this time,
	the original call will be hold.)

#### 3.5.7 Auto-Answer

You can set the phone and let it auto-answer the coming call.

Auto-Answer	the	1) Enable the Auto-Answer feature.			
Coming Call		2) Auto-Answer mode you can set in the MENU>Function			
		Setting> Auto Answer > Device			
		● Speaker			
		<ul><li>Handset</li></ul>			
		Headset			
		When you use the Handset mode, at this time you need to hands			

up the handset and then it can work at this status.
3)Filter Groups
Auto-answer the coming call in this special groups.

## 3.5.8 Ending a Call

To end a call, hang up. Here are some more details.

Hang up while using the	Return the handset to its cradle,
Handset	-or press <b>End</b>
Hang up while using the	Press <b>Speaker</b> button that is Red,
Speakerphone	-or press <b>Line</b> button for the appropriate line,
	-or press <b>End</b>
Hang up while using the	Press <b>Handset</b> button, (Do not keep the headset mode),
Headset	-or press <b>End</b> (keep the headset mode)
Hang up one call, but	Press <b>End</b> ,
preserve another call on	-or refer to the above three methods
the other line	

## 3.5.9 Using Hold and Recover (Switch Calling Line)

You can hold and resume calls. You can take a call in one line at anytime, and the other lines would be hold. As a result of that, you can switch different calling line on our phone.

If you want to	Then
Put a call on hold	Press <b>HOLD</b> button,
	-or press soft key Hold
Hold a line and switch to	Press another <b>Line</b> button for the appropriate line
another line	
Resume a call on current	Press <b>Line</b> button,

line														
Release	a	call	on	Select	the	line	want	to	release	hold,	press	the	line,	so
different I	ine			recove	ry;									

#### **NOTES**

- Engaging the Hold feature typically generates music or a beeping tone.
- A held call is indicated by the Yellow-green and flashing Line button or Hold in the LCD.

## 3.5.10 Transferring Calls

Transfer redirects a connected call. The target is the number to which you want to transfer the call.

Talk to the transfer	1) Press <b>TRANSFER</b> button or press XFER;
recipient before	2) Enter number;
transferring a call	3) press "#" (default) ,
(	-or press Send then transfer the call,
(consult transfer)	-or wait five seconds(default)then transfer the call
Transferred to idle	1) Press <b>TRANSFER</b> button or XFER;
lines or other	2) Press Blind;
numbers without	3) Enter number;
talking to the	4) Press "#" (default)
transfer recipient	-or press Send, then transfer the call;
(Blind transfer)	-or wait five seconds(default)then transfer the call
Blind transfer to the	1) Press <b>TRANSFER</b> button or press XFER;
held line	2) Press the <b>Line</b> button of held line

#### 3.5.11 Using Mute

With Mute enabled, you can hear other parties on a call but they cannot hear you. You can use mute in conjunction with the handset, speakerphone, or a headset.

	у станования при
Toggle Mute on	Press <b>C</b> button, then the screen top and left will have a MUTE
	icon

Toggle Mute off	Press <b>C</b> button again, then the button light off
-----------------	--

#### 3.5.12 Do Not Disturb

You can use the Do Not Disturb(DND) feature to block incoming calls on your phone with a busy tone (Can also be set to their voice mail or other extension numbers, etc.).

Enable global DND	1) Press <b>DND</b> ;
	2) All enabled line on the phone would changes to status.
	and the icon is DND.
Enable DND on a	Press <b>MENU</b> or <b>OK</b> button > "Function setting" > "DND" >
single line	(select line) "Enable"
Disable DND	Global DND enabled, press DND to disable global DND;
	Line DND enabled, press twice DND,
	-or press <b>MENU</b> or <b>OK</b> button > "Function setting" >
	"DND" >(select line) "Disable"

## 3.5.13 3-way Conference

You can enable a three-party conference, during the conversation three phone parties can communicate with every party.

If you want to	Then
Invite the transfer	1) When the transfer recipient answer the call, press
recipient into a	CONFERCENCE button or "CONF" on your phone;
conference in a	2) Then the held one, transfer recipient and you will be into a
transferring	conference, and the LCD will display conference 0:0:10
	status.
Invite the third party	1) Press "CONFERENCE" button or "CONF" in an active call;
into a conference in	2) Enter the third party number;
a active call	3) After connected the third party, press "CONFERENCE"
	button or "CONF" again

establish a	1) when one phone line is holding on and the other line is
conference with held	busy;
line	2) Press "CONFERENCE" button,
	-or Press "CONF" Soft key
	3)Press the held line's programmable button, the 3-way
	Conference is enable.

### **3.5.14 Voice Mail**

When the Phone get a voice mail from server. it will light up the voice mail button —.

	<u> </u>
Voice Mail	1) Press the Voice Mail button(There has Voice Mail icon
	,without is )
	2) Enter the User Password
	3) It will login into the voice mail server. You need to follow the
	IVR to do it.

## 3.6 Advanced Settings

## 3.6.1 Using the phone book

#### **Enterprise Phone Book**

Search the	1) Press DIR in the idle status,
Contacts from	-or press " <b>MENU"</b> or "OK" button > "Phone book">"Enterprise
Enterprise Phone	Phone Book",
Book	2) Select "Enterprise Phone Book", press " <b>OK"</b> button;
	3) Press "Find" and input the name who you want to search.
Call the Contact	1) Press "DIR" in the idle,
from Enterprise	-or press " <b>MENU"</b> or "OK" button > "Phone book">"Enterprise
Phone Book	Phone Book",
	2) Select "Enterprise Phone Book", press " <b>OK"</b> button;

- --3) Press "Find" and input the name who you want to search.
- --4) When you search the person, you can dial it.

### **Personal Phone Book**

A.I.C	1) 0 0 0
Add Contacts	1) Press Phone Book,
	-or press " <b>MENU"</b> button > "Phone book">"Personal phone
	book>View All",
	-or press " <b>OK"</b> button > "Phone book">"Personal phone
	book>View All";
	2) Select "Add contact", press " <b>OK"</b> button;
	3) Use the navigation keys to select content, press "OK" button
	to set and modify:
	-Name: set the name of contact,
	-Office Number: Setting the contact Office Number
	-Mobile Phone Number: Setting the contact Mobile Phone
	Number
	-Others Number: Setting the contact Others Number
	-SIP Account: Setting the contact call SIP account
	-Group: the contacts be divided into different user's groups
	4) Press "Save" soft key to complete
Add group	1) Press "DIR" soft key,
	-or press " <b>MENU"</b> button > "Phone book">"Personal phone
	book>View All",
	-or press " <b>OK"</b> button > "Phone book">"Personal phone
	book>View All";
	2) Select the "add group" then press <b>OK</b> button;
	3) Use the navigation keys to select content, press <b>OK</b> button

	to set and modify:
	-Group name: name of the group
	4) Press "Save "soft key to complete
Modify group	1) Press "DIR" soft key,
	-or press " <b>MENU"</b> button > "Phone book">"Personal phone
	book>View All",
	-or press " <b>OK"</b> button > "Phone book">"Personal phone
	book>View All";
	2) Select the "Modify group" then press " <b>OK"</b> button;
	3) Select the group you want to modify, press the " <b>OK"</b> button
	to set and modify, press "Save" to save the change
Delete group	1) Press "DIR" soft key,
	-or press " <b>MENU"</b> button > "Phone book">"Personal phone
	book>View All",
	-or press " <b>OK"</b> button > "Phone book">"Personal phone
	book>View All";
	2) Select the "Delete group" or <b>OK</b> button;
	3) Select a group you want to delete, press <b>OK</b> button

#### **LDAP**

Search	the	1) Press "DIR" in the idle,
Contacts	from	-or press " <b>MENU"</b> or OK "button" > "Phone book">"LDAP",
LDAP		2) Select "LDAP", press " <b>OK"</b> button;
		3) Press "Find" and input the name or number who you want to
		find search from the LDAP server.
Call the	Contact	1) Press "DIR" in the idle,
from LDAF	•	-or press " <b>MENU"</b> or "OK" button > "Phone book">"LDAP",

2) Select "LDAP", press " <b>OK"</b> button;
3) Press "Find" and input the name or number who you want to
find from the LDAP server.
4) When you search the person, you can dial it.

#### **Black List**

Add the Contacts	1) Press "DIR" in the idle,
	-or press " <b>MENU"</b> or "OK" button > "Phone book">"Black
	List",
	2) Select "Black List", press " <b>OK"</b> button;
	3) Press "Add" and input the name\office number\mobile
	number\other number\SIP account who what you want to add
	into the Black List.
View the Contact	1) Press "DIR" in the idle,
from Black List	-or press " <b>MENU"</b> or "OK" button > "Phone book">"Black
	List",
	2) Select "Black List", press " <b>OK"</b> button;
	3) Press "RUN" to view someone who what you want to find.
	4)If you want to move or change it, you can follow the RUN to
	do.

# 3.6.2 Using Call Logs

Your phone maintains records of your missed, placed, and received calls.

View call logs		1) Press "MENU" or "LOG" button > "All Call" > "Missed
		Calls", "Received Calls", or "Dialed numbers"
		2) Use the navigation keys to view the call record information.
Delete/Save	Call	1) Login in to the Call Logs

Logs	2) Use the navigation keys to view the call record or select DEL
	key.
	3) Use the navigation keys to view the call record or select Save
	key.

#### 3.6.3 Peer-to-Peer

When all of the phone accounts were disable or not register. it will be show this mode in the idle. It can use by when the new workstation isn't have SIP server.

Peer-to-Peer	Disable all of accounts or not register.
Make Call with	1) Press OK or MENU button> System Setting> Advanced Setting>
Peer-to-Peer	SIP Account;
	2) Disable all of accounts or un-register;
	3) Turn back the phone idle, you can call someone use IP address.

## 3.7 Keypad Setting

SayHi series IP Phone can through two ways configuration it, one is setting in MENU, another is setting in website. Here just description in MENU.

NOTES: When you want to input the IP address like ".", it was replaced by the "\*".

## 3.7.1 Language Setting

ES290 IP Phone support Multi-Language setting, as below is an example.

	3 3 37 1
Switch the Language	1) Press OK or MENU button> System Setting> Phone Setting>
between Chinese and	Language
English	2) Here you can select
	English\French\Italian\Polish\Protuguese\Runssian\Spanish\
	Turkish\Chinese
	3) After you finish select, press Save to make it work.

## 3.7.2 Message

ES290 have Message feature. It will display in the LCD when it has a New Message.

	1 7
Create a	1) Press OK or MENU button;
	2) Select "Messaging"
Message	3) Voice Message: Setting the Voice Message code in here.
	Text Message: Write down the Text Message in here.
	4) Select Text Message> New Message.
	5) Input the receiver and write down message body, and then
	press send to finish.
Message Inbox	1) Select Message Inbox.
	2) Select which one you want to check.
	3) You can press Enter to read or press Del to delete.

## 3.7.3 Time & Date

SNTP	1) Press OK or MENU button;
	2) Press OK or MENU button> System Setting> Phone Setting> Time &
	Date> Time and Date setting> SNTP
	3) SNTP
	- <b>Time Zone</b> : Setting the time zone
	-NTP Server 1: NTP server address 1
	-NTP Server 2: NTP server address 2
	- <b>DayLight</b> : Enable/Disable Day Light
SIP Server	1) Press OK or MENU button;
	2) Press OK or MENU button> System Setting> Phone Setting> Time &
	Date> Time and Date setting>SIP Server
	3) Press Save to make it work
Manual	Press OK or MENU button;
	2) Press OK or MENU button> System Setting> Phone Setting> Time &
Setting	Date> Time and Date setting> Manual Setting
	3) Manual Setting
	<ul><li>- Manual Setting: Year\Month\Days\Hours\Minutes\Seconds</li></ul>
Time Display	1) Press OK or MENU button;
	2) Press OK or MENU button> System Setting> Phone Setting> Time &
Format	Date> Time Display Format
	3) Time Mode: 24hour\12hour
	Date mode:
	DDMMWWW\MMDDWWW\WWWDDMMM\DDMMMYY\YYYYMMDD\DD
	MMYYYY\MMDDYY\DDMMMYYYY\WWWDDMMM etc.

## 3.7.4 Ring Tone and Volume Setting

Ring Type	1) Press OK or MENU button;
Tang 1,pc	2) Press OK or MENU button> System Setting> Phone Setting>Ring
	Туре
	3) Select the ring type from 1 to 8 or custom ring, and then press Save
	to make it work.
Volume	1) Press OK or MENU button;
	2)Press OK or MENU button> System Setting> Phone Setting> Volume
Setting	Setting
	3) Volume Setting: Handset\Speaker\Headset\Ring volume
	4) Press Enter to adjust the volume and press Save to make it work

NOTES: For the Custom Ring Type you need to upload it from website.

## **3.7.5 Searching Phone Book**

Accurate Search	1) Press <b>MENU</b> or <b>OK</b> button > "Function Setting", you can select " Accurate Search "
	2) Then press Enable/Disable and Save.
	3) When you back to idle, you can use the digital keypad to search the contact.
T9 Search	1) Press <b>MENU</b> or <b>OK</b> button > "Function Setting", you can select
	" T9 search"
	2) Then press Enable/Disable and Save.
	3) When you back to idle, you can use the digital keypad to search the contact.

NOTES: The Search Phone Book setting default is Accurate Search.

## 3.7.6 Cannot Set the Features with Keypad

As below features are cannot setting with the keypad:


- 1) Dial Plan.
- 2) Custom Ring Type
- 3) SNTP Server and Time & Date
- 4) Update the Firmware or Backup.

### 4. WEB User Interface

In addition to the phone user interface, you can also customize your phone via web user interface. In order to access the web user interface, you need to know the IP address of your new phone. To obtain the IP address, press the C key on the phone. Enter the IP address (e.g. HTTP://192.168.0.10 or 192.168.0.10) in the address bar of web browser on your PC. The default user name is root (case-sensitive) and the password is root (case-sensitive).

#### **Main Interface-Phone Status**

Here you can see as below information: System Run Time, Register Status, Network Status, System Information,



ITEM	DESCRIPTION
System Run Time	The phone system normal running time.
Register Status	The status with Account 1~3.
Network Status	The status with LAN, MAC, LAN IP, Net mask, Gateway, Primary
	DNS, Secondary DNS, VPN IP, PC IP, PC Net mask, Device Type,
	DHCP Server.
System Information	The status with Phone Model, Software Version, Hardware
	Version, Hardware ID, Kernel Version, Auto-Provision Server URL,


www.escene.ru

TFTP Server IP.

#### 4.1 Net Work

#### **4.1.1 LAN Port**

#### **Basic**



ITEM	DESCRIPTION
Network Connection Mode	Network Connection Mode has DHCP, Static IP, PPPoE.
DNS Settings	Select the DNS mode that you want.

#### **Advanced**

Port Management Settings	
HTTP Port	80
Telnet Port	23
Socket5 Proxy Server	
Socket5 Proxy Server	● off ○ on
Server IP	*
Port	1080 *
Anonymous Login	✓
Username	
Password	
Paging Setting	
Paging 1	● off ○ on
Group IP	Port: 10000
Paging 2	● off ○ on
Group IP	Port: 10000
Paging 3	● off ○ on
Group IP	Port: 10000
Paging 4	● off ○ on
Group IP	Port: 10000
Paging 5	● off ○ on
Group IP	Port: 10000
	Port (80) will require using the new port number to access the IP anges require a reboot. Use the following format when not using the

ITEM	DESCRIPTION
Port Management Settings	
HTTP Port	The default web port is 80,if you want to change it(for example change it to88),  You must input IP and Web port to login the web page(for example HTTP://192.168.0.200:88). It will take effect on
	next reboot.
Telnet Port	The default Telnet port is 23,if you want to change it(for example change it to 2003). You must input IP and Telnet port to login the manage page (for example telnet 192.168.0.200:2003). It will take effect on next reboot.

default HTTP (http://ip address:portnumner).

Socket5 Proxy Server		
Socket5 Proxy Server	Enable/Disable Socket5 Proxy Server.	
Server IP	Socket5 Proxy Server IP address.	
Port	Socket5 Proxy Server port, default is 1080.	
Anonymous Login	Enable/Disable Socket5 Proxy Server login username.	
Paging Setting(NOTE: This feature priority is followed the serial number, In		
other words, "paging 1" is the highest priority)		
Paging1	Enable/Disable Paging feature.	
Group IP and Port	Group IP and Port with Paging.	

#### 4.1.2 PC Port

Normally choose Bridge, if you choose Router ,you need to input router IP address ,net mask.



#### **Bridge**

Normally, you should choose "bridge" feature, it means that pc port and LAN port will share the same network.

#### **Router**

Router feature is for the phone PC Port. You must input IP address (it's equivalent to a gateway) and Net mask. If you want to use DHCP function, please turn it on, input start IP and end IP.

#### 4.1.3 Advanced

#### **VPN Setting**



When using VPN Setting option, you can set several parameters as follow:

VLAN Setting	
Enable VPN	You can enable/disable VPN for phone and pc.
VPN Type:	Choose the appropriate type of VPN.
VPN Server Addr	VPN server's IP.
VPN User Name	VPN user's name
VPN Password	A password be used for authentication

#### **VLAN Setting**



When using VLAN Setting option, you can set several parameters as follow:

VLAN Setting	
Enable VLAN	You can enable/disable vlan for phone and pc
VID	The vlan ID you want the phone or pc to join
[LAN/PC Port]	

# **5 SIP Account**

## 5.1Basic

Enable	✓ •
Account Mode	VOIP 🗸
Amount Of Line Account Used	1 ( Default: 2)
Display Name	<b>@</b>
Username	5207 * 🕜
Authenticate Name	5207
Password	· · · ·
Label	•
SIP Server	192.168.0.7
Secondary server	•
OutboundProxy Server	•
Secondary OutboundProxy Server	•
Polling Interval Time Of Registration	32 s Default Value: 32s, Range: 20s~~60s
NAT Traversal	Disable V
STUN Server	•
BLA	● off ○ on
BLA Number	
Subscribe Period	1800 Default: 1800s, Min: 120s 🕜
Register Expire Time	3600 Default: 3600s, Min: 40s 🕜
Auto Answer	● off ○ on
SIP Transport	● UDP ○ TCP ○ TLS 🚱
Ring Type	None ✓ ②

Choose one Account, you will find the following parameters:

	5 1
ITEM	DECSRIPTIO
Enable	You can choose on/off to enable/disable the line.
Account Mode	You can choose VOIP/PSTN, but this model nonsupport PSTN, If you
	need, Pls contact us to buy another model that can supports PSTN.
Amount Of Line	The line key of account used, default is 2
Account Used	
Display Name	It is showed as Caller ID when making a phone call

Username	It is a username provided by SIP Server
Authenticate Name	It is authenticated ID for authentication
Password	It is a password provided by SIP Server
Label	Label with this account.
SIP Server	Server for registration, provided by administrator
Secondary server	When the main server can't work, it also can register in this secondary server.
Outbound Proxy	Put into the address with the outbound proxy server.
Secondary Outbound Proxy Server	When the main out bound server can't work, it also can use this secondary server.
Poling Interval Time Of	Poling Interval Time Of Registration, default is 32 s.
Registration	
NAT Traversal	Defines the STUN server will be active or not
STUN Server	Session traversal utilities for NAT.
BLA	Share with the line.
BLA Number	BLA Number
Subscribe Period	Subscribe expire time.
Register Expire Time	IP phone automatically registered every time
SIP Transport	There are UDP/TCP/TLS three options
Ring Type	Select this account ringing type.

## **5.2 Call**

Do Not Disturb	$left$ off $\bigcirc$ on
Anonymous Call	● off ○ on
Anonymous Call Rejection	● off ○ on 🚱
Use Session Timer	$\odot$ off $\bigcirc$ on
Session Timer	300 (min:150s)
Call Method	● SIP ○ TEL
DNS-SRV	$\odot$ off $\bigcirc$ on
Allow-events	$\odot$ off $\bigcirc$ on
Registered NAT	○ off ● on
UDP Keep-alive Message	$\odot$ off $\bigcirc$ on
UDP Keep-alive Interval	30 (15-60s)

ITEM	DECSRIPTIO
Call	
Do Not Disturb	Enable/Disable Do Not Disturb
Anonymous Call	Enable/Disable anonymous call.
Anonymous Call Rejection	Enable/Disable anonymous call rejection.
Use Session Timer	Enable/Disable refresh session function. The device will send an Invite packet to refresh the session during a call if it enable.
Session Timer	The refresh session time interval.
Call Method	This method include SIP and TEL.
DNS-SRV	Enable/Disable DNS-SRV.
Allow-events	Enable/Disable Allow-events.
Registered NAT	Enable/Disable Registered to NAT
UDP Keep-alive	The phone periodically sends a UDP packet to keep the port active
Message	and to avoid the server to shut down the port
UDP Keep-alive Interval	Default is 30 second.

## **5.3 Security**



ITEM	DECSRIPTIO
Security	
SIP Encryption	Enable/Disable SIP encryption.
RTP Encryption	Enable/Disable RTP encryption.
Encryption Algorithm	The encryption algorithm at this time we only have RC4.
Encryption Key	The key with encryption.

# **6 Phone Setting**


## 6.1 Basic

BackLight	○ off ○ Always On ● timer 60 s (Min:1, Max:255)
Keyboard Lock	Disabled V
Hot Line Function	● off ○ Delay 5 s (0-30)
Hot Number	•
Auto Answer	● off ○ on ○ Turn On But Filter This Group: NONE ✔
Auto Answer Mode	Hands Free      Handle      Headset
Call Waiting	○ off ● on 🕜
Call Waiting Tone	O off ● Play on currently active device Frequency: 10 s (5-60)
DTMF	● RFC 2833 ○ Inband ○ SIP Info ○ Auto ②
Fuzzy Search	● off ○ on
Phonebook Search	<ul><li>● Accurate Search ○ T9</li></ul>
Call List Save	O off ● on
Network Packet Mirroring	Off ∨

ITEM	DECSRIPTIO
Basic	
Back Light	The backlight of the phone LCD.
Keyboard Lock	Enable/Disable keyboard lock, you can lock: MENU Key, FUNCTION Key., ALL Keys, LOCK all keys but auto Answer.
Hot Line function	When you pick up the handset, it will dial out with the hot number.
Hot Number	Input the number what you want to.
Auto Answer	Auto-answer the coming call, it also can filter a contact group.
Auto Answer Mode	Auto-answer the coming call, it also can filter a device to answer.
Call Waiting	When there's coming a call or the phone is talking, the second call will be in the queue.
Call Waiting Tone	Select the frequency with the tone when call waiting.
DTMF	The DTMF transmitted mode, include RFC2833, Inband, SIP Info, Auto
Fuzzy Search	Fuzzy search someone with the phone book in the idle.
Phone Book Search	Enable/Disable the phone book search feature with accurate or T9 mode.
Call List Save	You can choose to save the call list into the phone or not.
Network Packet Mirroring	When select on, then you can capture the phone's packet use notebook which connect to pc port of the phone


www.escene.ru

## **6.1.1 Time Settings**



ITEM	DECSRIPTIO
Time Settings	
Set Time Mode	Include SNTP/SIP Server/PSTN/Manual
SNTP Server	You can select in the list or input owner server address.
Update Interval	The update interval with SNTP.
Day Light Saving Time	Enable/disable the DST for the phone
Time Format	You can use 24 hour time format or 12 hour time format
Date Format	You can choose the appropriate time format.
Time Zone-GMT	You can select different time zone for the phone
Manual Setting	Setting time manually.


#### 6.1.2 Call



ITEM	DECSRIPTI
Call	
Pickup Function	When you are not in the position, others can help you to answer.
Pickup Code	Fill in server's pickup code.
Message	The code with voice message.
Booking Voice Mail	Open this feature, the phone light(Message) will be bright when it get message.
Play Voice Mail Tone	Open this feature, it will be ringing when it get message.
Miss Call Display	Turn on or off the display with Miss call in the phone LCD.

DND Soft key	Enable/Disable the DND feature.
Play Hang-up Tone	The tone with hang up in busy.
Transfer Code	The code with transfer.
Conference Exit Result	Conference originator hang up the phone, hang up two ways of it.
Return Code When Refuse	Select the code feedback to the server when you reject the call.
Return Code When DND	Select the code feedback to the server when you open DND function.
Flash Hook Time(<800ms)	The time with the flash hook.
Called No Answer Time	When it has coming call and enable this feature, the caller will be request time out in the stipulated time.
Pound Send Method	When you to use the code, such as: #28#123 or %23123, you need to set this feature.
RFC 2833 Play Load	Default is 101, RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals
P-Asserted-Identity	Enable/Disable the P-Asserted-Identity feature.
SIP Session Timer T1	The SIP Session Timer setting.
SIP Session Timer T2	The SIP Session Timer setting.
SIP Session Timer T4	The SIP Session Timer setting.
Local SIP Port	The port range setting with SIP, default is 5060.
RTP Port Range	The port range with RTP
Affiliated Port	Enable/Disable the affiliated port feature.
Headset Mode	Select headset mode with normal or seat.
Ring Type On Seat Mode	Select ring type mode with headset or speaker.

## **6.1.3 VoIP Call Forward**



ITEM	DECSRIPTIO
Always	All ways transfer the call to others.

If Busy	If the phone was busy working, the call will be transfer to others.
If No Answer	If the phone was no answer, the call will be transfer to others.
Ring Frequency	The ring frequency with the VOIP Call Forward.

## 6.1.4 QoS

SIP Qos	26	(0-63)
Voice Qos	46	(0-63)

ITEM	DECSRIPTIO
SIP QoS	The range is 0~63,default is 26
Voice QoS	The range is 0~63,default is 46

#### 6.2 Advanced

#### 6.2.0 Audio


#### 6.2.1 Basic



ITEM	DECSRIPTIO
Basic	
Select Country	Select the country dial tone. Default is United States.

Ring Volume	The ring volume default is Lv3, the range is 0~9.
Handset Volume	The handset volume default is Lv5, the range is 1~9.
Speaker Phone Volume	The speaker volume default is Lv5, the range is 1~9.
Headset Volume	The headset volume default is Lv3, the range is 1~9.
Handset MIC Volume	The handset MIC volume default is Lv3, the range is 1~7.
Speaker Phone MIC Volume	The speaker MIC volume default is Lv3, the range is 1~7
Headset MIC Volume	The headset MIC volume default is Lv3, the range is 1~7

#### 6.2.2 Advanced




ITEM	DECSRIPTIO	
Ring		
Ring Type	Select the ring type. Default is Ring 1.	
Uploading Ring Tone	Please upload a ring tone with G711A audio coding, Maximum 10 rings and the total sizes must less than 150k.	

www.escene.ru

	<del>-</del>	
Audio Codec	Use the navigation keys to highlight the desired one in the	
	Enabled/Disable Codes list, and press the >>/ << to move to	
	the other list.	
Jitter Buffer		
Туре	The type of Jitter Buffer is Adaptive or Fixed, default is adaptive.	
Min Delay	The min delay range setting , default is 60.	
Max Delay	The max delay range setting , default is 150.	
Normal Delay	The normal delay range setting, default is 120.	
Other		
Play Load Length	The play load length setting, default is 30ms.	
High Rate Of G723.1	Enable/Disable High Rate of G723.1 feature.	
VAD	Enable/Disable VAD feature.	
Echo Suppression	Enable/Disable Echo Suppression Mode feature.	
Mode		
Side Tone	Enable/Disable Side Tone feature.	

# 6.3 Line Keys




DTMF	You can use this key feature to send the specification of arbitrary key
	sequences via DTMF.
BLF	You can use the BLF feature to monitor a specific user for status changes
	on the phone.
Paging	You can use multicast paging to quickly and easily forward time sensitive
	announcements out to people within the multicast group.
Call Park	You can use call park feature to place a call on hold, and then retrieve
	the call from another phone in the system (for example, a phone in
	another office or conference room).
Intercom	You can press the configured intercom key to automatically connect with
	a remote extension for outgoing intercom calls, and the remote
	extension will automatically answer the incoming intercom calls
BLA	This feature such as the BLF.

NOTE: ONLY WHEN YOU CHOOSE "SPEED DIAL", THE RIGHT OF "NAME","NUMBER" WILL TAKE EFFECT.

## 6.4 Function Keys


Function Keys: If you do not like the default setting with the function keys feature. You can change to whatever you like.

NOTE: IF THE PHONE WITHOUT THE KEY, YOU CAN IGNORE IT.



## 6.5 Soft Key

Soft Keys: Soft key is the key with below display in the LCD. You can change it for your mind to the other features in many all kinds of status. As below example, when you dialing with someone, the LCD display soft key is Send \Del \Empty\End, Empty means nothing in it.



#### 6.6 Dial Plan

If you want to setup a dial plan, you can click "Dial Plan"



ITEM	DECSRIPTIO	
Send Key	Select the default send key mode you want to use.	
Dial Length	Enable this feature will limit the dial length. Default is 25.	
No Dial Timeout	Setting the range with no dial timeout, default is 5.	
Dial Rule	Select the Add Rule button to add dial rule, pls see as below detail.	

ID	1 🗸	Description	
IP		Port(Default 5060)	5060
Prefix			
Called Insert Number	Disable V	Called Delete Number	Disable V
Position		Position	
Number		Length	
	(Note: When you want to add co first, after that base on the numb delete code.)		

ITEM	DECSRIPTIO	
ID	Dial Plan ID	
IP	The ip of a phone which you want to call	
Description	Description with this dial rule.	
Port	Setting the Port with this dial rule, default is 5060.	
Prefix	The number which you need to press actually if you want to call the	
	phone	
Called Insert Number	There have two option, Enable or Disable.	
Position	Which position you want insert the number	
Number	Which number you want to insert	
Called Delete Number	There have two option, Enable or Disable.	

NOTES: If you want to know more detail about Dial Rule, pls find it in the official website to download the specific document. HTTP://www.escene.cn/en.

# 6.7 IP Strategy

You can use IP Strategy feature to make a list which can be set to only allow the incoming call on the list.

e.g. As following picture you can see it has 192.168.0.248 in the list. When you open this feature. It means you just allow come from this IP address meeting




# 7 Phone Book

The phone book including Group, Contact, LDAP and Ban list, please review the following for more details:

## **7.1 Group**

You can add, edit and delete group in a phone book on this web page.



If you want to add a Group, you just ought to click 'Add Group'.


You can edit an existed Group by click .

You can delete an existed Group by click  $\overline{m}$ , if you want to delete all Groups, you just ought to click 'Delete All Group'.

## 7.2 Contact

You can add, edit and delete contact in a phone book on this web page.

The phonebook can storage 300 contacts entry





If you want to add a Contact, you just ought to click 'Add Contact' .

You can edit an existed Contact by click .

You can delete an existed Contact by click  $\overline{m}$ , if you want to delete all Contacts, you just ought to click 'Delete All Contact'.

You can edit or move this contact to Ban List after you select <a>I</a>.

You can download and save this contact to PC after you select .

#### **7.3 LDAP**

NOTES: If you want to know more detail about LDAP, pls find it in the office website to download the specific document. HTTP://www.escene.cn/en. As below figure is an example.

e.g.

LDAP Name Filter:(sn=%s)


LDAP Number Filter:(telephoneNumber=%s)

Server Address:192.168.0.65

BASE:DC=ldap,DC=escene,DC=com User Name: bb@ldap.escene.com


Pass Word: escene\_2012 LDAP Name Attributes 1:sn LDAP Name Attributes 2:cn

LDAP Number Attributes 1:telephoneNumber



#### 7.4 Ban List

You can add, edit and delete contact in a Ban List on this web page.





If you want to add a Ban List, you just ought to click 'Add Ban List'.

You can edit an existed Ban List by click .

You can delete an existed Ban List by click  $\overline{m}$ , if you want to delete all Ban List, you just ought to click 'Delete All Ban List'.

You can edit or move this contact to Contact after you select <a> </a>.


## **8 Phone Maintenance**

#### 8.1 Basic

NOTES: Don't cut off the electricity or network cable when doing upgrade in the below ways!

## 8.1.1 HTTP Upgrade

You can upgrade the software, kernel and configuration etc. files by HTTP.




When using HTTP upgrade, you can set several parameters as follow:

HTTP Upgrade

Select a File	Browse the software/kernel/configuration file which you need to
	upgrade from HTTP
Software	Used for upgrading the software of the phone
Upgrade	
Kernel Upgrade	Used for upgrading the kernel of the phone
Configuration	You can used upload/download to upload/download the configure file
	of the phone
XML Phone	Used for uploading/downloading the XML phonebook of the phone
Book	
Vcard	Downloading all contacts in the Vcard mode, but upload only support
	one by one.
EXT Module	Used for updating/backup the expansion of the phone
	[NOTES: The mode doesn't support this feature]
Log	Used for the administrator to find out or making sure the problem
	with this equipment.
All Config File	All Config File includes: Configuration, Extern, Log, XML Phone book,
	Enterprise Phone Book.

# 8.1.2 FTP Upgrade

You can upgrade the software, kernel and configure files by FTP.



When using FTP upgrade, you can set several parameters as follow:


FTP Upgrade	
Server IP	The IP address of the FTP server

Filename	Downloading from FTP server	
Username	Providing by FTP server	
Password	Providing by FTP server	
Software Upgrade	Used for upgrading the software of the phone	
Kernel Upgrade	Used for upgrading the kernel of the phone	
Configuration	Used for updating/backup to update/backup the configure file of	
	the phone	
Phone Book	Used for updating/backup to update/backup the phonebook of the	
	phone	
EXT Module	Used for updating/backup the expansion of the phone	
	[NOTES: The mode doesn't support this feature]	

NOTES: It's not necessary to input filename when doing backup Configuration, Phone Book, EXT Module.

# 8.1.3 TFTP Upgrade

You can upgrade the software, kernel and configure files by TFTP.



When use TFTP upgrade, you can set several parameters as follow:

TFTP Upgrade		
Server IP	The IP address of the TFTP server	
Filename	Downloading from FTP server	
Software Upgrade	Used for upgrading the software of the phone	
Kernel Upgrade	Used for upgrading the kernel of the phone	
Configuration	Used for updating/backup the configure file of the phone	
Phone Book	Used for updating/backup the phonebook of the phone	
EXT Module	Used for updating/backup the expansion of the phone  [NOTES: The mode doesn't support this feature]	

NOTES: It's not necessary to input filename when doing backup Configuration, Phone Book, EXT Module.

## 8.1.4 Default Setting


You can load the phone to the factory default setting in default setting option.



Press the 'Reset to Factory Setting' option, the phone will load to factory default setting on next reboot.

#### **8.1.5** Reboot


You can use reboot option to reboot the phone.



## 8.2 Advanced


## 8.2.1 Log

This feature is use for the administrator to managing the equipment, like debugging, SIP etc,. If you need to catch a debugging Level, you need to setup on this interface.



#### 8.2.2 Auto Provision

When you open this auto provision feature, the phone will do auto provision after it detect a different software or kernel (Higher or Lower) which are putted on the TFTP,HTTPS,FTP, server. For the detailed information about auto provision, you can find it in the official website: HTTP://www.escene.cn/en




When using auto provision, you can set several parameters as follow:

<b>Auto Provision</b>	
Auto Provision	You can enable/disable auto provision by select on/off
Protocol	Used for auto provision, it includes TFTP/HTTP/FTP
Software Server URL	The server address of the auto provision
Username	Providing by provision server
Password	Providing by provision server
Auto Download Software	Used for auto download software from server
Auto Download Kernel	Used for auto download kernel from server
Auto Download Config File	Used for auto download config file from server
Auto Download Expansion	NOTES: The model doesn't support this feature.
Auto Download Enterprise	Used for auto download Enterprise Phonebook from server
Phonebook	

Auto Download Personal	Used for auto download personal phonebook from server
Phonebook	
Booting Checked	Used for checking the auto provision when phone booting
Disable the phone while	Enable/Disable the booting checking feature.
booting checking	
Auto Provision Frequency	Used for setting the time interval for auto provision
Auto Provision Time	Used for the specific time for auto provision
Auto Provision Next Time	Reset the Auto Provision Next Upgrading time.
AES Enable	You can enable/disable AES encrypt for auto provision
AES Key	The key of the AES
Auto Provision Now	Used for doing auto provision immediately

# 9 Password


Here you can setting the administrator or user WEB password management. Select your type. If you login as an administrator, you can modify both the user's and admin's passwords.



# 10 WEB Other Settings or Information - Appendix

## 10.1 WEB User

In the upper right corner of the website page, you can select the user or logout.



# 10.2 Multi-Language

In the upper right corner of the website page, you can select the language in the below list.



## 10.3 Note Tips

In the right middle of the website page, there is a Note tips in every function page. Hope it can help you to know something about that.

