


Hybrid DVR

# 8 CH Hybrid DVR



## SM-XVS1801L2



HD Output



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse



E-mail

SM-XVS1801L2 is a 8 CH 720P high definition DVR with ability to connect analog and IP cameras simultaneously, which adopts the standard H.265 high profile compression format and the advanced SOC technique to ensure real time recording in each channel and realize outstanding robustness of the system. SM-XVS1801L2 supports 8CH video input, 1 CH audio input, simultaneous 8 CH playback.


The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



## Features


- 8 CH TVI/ AHD/ CVI 1080P/ 1080P Lite/ 720P/ 720P Lite/ WD1 video input
- 8CH DVR supports 2 CH IP video input by default
- 8CH DVR: 8CH analog video input can be switched to 8CH IP video input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse
- Multi-mode recording: manual / timed / motion / AI recording
- Playback :8CH simultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

## DIMENSIONS



## Rear Panel

SM-XVS1801L2



## SPECIFICATIONS

Model			
System	OS	Embedded Linux	<b>M-XVS1801L2</b>
Video	Analog Video Input		BNC × 8
		BNC interface (1.0Vp-p; 75Ω)	
		TVI/AHD/CVI: 1080P/1080P Lite/720P/720P Lite/WD1	
	IP Video Input		2CH(up to 10CH)
		U	Up to 5MP@25fps
	Total Input		10CH
	Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768	
	Compression	H.264/H.265	
Audio	Multi-screen Display		1/4/6/8/9/13/16
	Input	RCA × 1	
	Output	RCA × 1 (linear, 600Ω)	
	Two-way audio	Take up channel one audio input	
Record	Compression	G.711(U/A)	
	Resolution		1080P Lite/720P/720P Lite/WD1
	Frame Rate	Analog Channel: 8CH DVR: 1080P Lite/720P/WD1: 25fps (PAL)/30fps (NTSC) ( only CH 1 supports) 1080P Lite/720P/WD1: 12fps (PAL)/15fps (NTSC) ( other channels support) 720PLite: 25fps(PAL) / 30fps (NTSC) IP Channel: 25fps(PAL) / 30fps (NTSC)	
	Bit Rate	32Kbps ~ 4Mbps	
Playback	Playback		8CH
	Search	Time slice / time / event / tag search	
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events	
	Function	Play, pause, FF, FB, digital zoom, etc.	
Alarm	Mode	Manual, motion, exception, smart event	
	Input	No	
	Output	No	
Network	Interface	RJ 45 100Mbps × 1	
	Protocol	TCP/IP, HTTP, HTTPS, 802.1x, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, UDP, WebSocket, PPPoE, SNMP, IGMP	
	Incoming Bandwidth		16Mbps
	Outgoing Bandwidth		60Mbps
	Client Connection	Max. 5 users access	
MobileDevice	OS	iOS, Andriod	
Storage	HDD	SATA × 1, up to 8TB	
Backup	Local Backup	U disk, USB mobile HDD	
	Network Backup	Yes	
Port	RS 485	No	
	USB	USB 2.0 × 2	
	Remote Controller	No	
Others	Power Supply	DC12V / 1.5A	
	Consumption	≤ 5W ( without HDD )	
	Dimensions(mm)	255 × 222 × 42 ( W × D × H )	
	Working Environment	-10~50°C, 10%~90% (humidity)	
	Certificate	CE, FCC	
	Environment Protection	Directive EU RoHS, WEEE, REACH	